

MIDFIX QWIKCLAMP – UNLINED

Product Description

Qwikclamps are two-piece electro zinc plated steel pipe clamps with a ribbed profiling for optimal strength. They have welded bosses with M8/M10 dual-tapped threads throughout the range and hexagon combi-drive screws for easy tightening. The comprehensive range covers all pipe diameters from 9mm to 250mm.

Applications

Qwikclamps are designed for supporting medium load pipework in building services installations. Unlined Qwikclamps are used with phenolic, Rockwool and wooden pipe support blocks for supporting insulated pipes and with uninsulated steel and plastic drainage pipes. Qwikclamps are recommended for internal use and tested for supporting static pipe loads in tension.

Features

- Material: Steel
- Finish: Electro Zinc Plated - 8µm minimum coating thickness
- M8/M10 Welded Boss
- Screws: Hexagon head with combi drive fitted with plastic retaining washers – for use with hex, Philips or slotted drivers
- Product Identification: Stamped with MIDFIX QWIKCLAMP
- Loads: Tested for safe static tensile loads – see product table for loads.



MIDFIX QWIKCLAMP – UNLINED

Product Data

DESCRIPTION	STOCK CODE	PIPE O.D. (MM)	STEEL SIZE	MAT. SIZE	SCREW SIZE	*LOAD (KN)	BOX QTY
QU018	1105018	15-20	3/8"	1x20	M6 x 20	0.7	300
QU022	1105022	19-23	1/2"	1x20	M6 x 20	0.7	150
QU028	1105028	26-30	3/4"	1x20	M6 x 20	0.7	100
QU035	1105035	32-35	1"	1x20	M6 x 20	0.7	125
QU040	1105040	39-43	1.1/4"	1x20	M6 x 20	0.7	150
QU048	1105048	45-51	1.1/2"	1.2x20	M6 x 20	0.7	100
QU054	1105054	54-58		1.2x20	M6 x 20	0.7	100
QU060	1105060	60-65	2"	1.2x20	M6 x 20	0.7	100
QU070	1105070	67-71		1.2x20	M6 x 30	0.7	50
QU075	1105075	74-82	2.1/2"	1.5x25	M6 x 30	1.0	50
QU083	1105083	82-89		1.5x25	M6 x 30	1.0	50
QU090	1105090	91-98	3"	1.5x25	M6 x 30	1.0	50
QU100	1105100	93-101	3.1/2"	1.5x25	M6 x 30	1.0	30
QU105	1105105	102-109		1.5x25	M6 x 30	1.0	30
QU110	1105110	109-117	4"	1.5x25	M6 x 30	1.0	50
QU125	1105125	116-125		1.5x25	M6 x 30	1.0	50
QU133	1105133	129-141		2x25	M6 x 30	1.2	50
QU140	1105140	136-146	5"	2x25	M6 x 30	1.2	40
QU150	1105150	142-154		2x25	M6 x 30	1.2	25
QU160	1105160	158-169	6"	2x25	M6 x 30	1.2	30
QU180	1105180	166-177		2x25	M6 x 30	1.2	20
QU200	1105200	201-212		2x25	M6 x 30	1.2	15
QU220	1105220	219-229	8"	2x25	M6 x 30	1.2	15
QU250	1105250	245-254		2.3x19	M6 x 30	1.2	25

*Safe static tensile load with limited deflection